

SV II



In touch with nature.

*Kowa*

# SV II



Where value meets quality. A range of affordable optics without compromise.



- Waterproof and dry nitrogen filled
- Ergonomic styling
- Lightweight body
- Fully multi-coated optics
- KR protective coating
- Easy to use
- Superb value



**Easy to use:**  
Large responsive focus wheel.



**Easy to adjust:**  
Tailor to suit your viewing needs.



**Bright and clear:**  
Fully multi-coated optics.



**Portable:**  
Lightweight ergonomic body.

Kowa have infused over half a century of heritage in optical design and manufacture to develop a range of high quality, affordable optics in the stylish SV II range.

Featuring fully, multi-coated optics, The SV-II range deliver a bright and clear image with natural colour and contrast.

Easy to operate with large a responsive focus wheel, ergonomic design and lightweight robust materials delivering an optic that represents superb value / performance ratio and a joy to use.

A tough polycarbonate, fully waterproof and nitrogen filled body makes these binoculars perfectly at home in the great outdoors whatever the weather. Kowa's unique KR coating also repels dirt and residue from building up on the lenses.

The SV-II range include a high quality padded case and neck strap plus objective and eyepiece protective caps.

## SPECIFICATION

	SV50-12	SV50-10	SV42-10	SV42-8	SV32-10	SV32-8	SV25-10	SV25-8
Magnification	12x	10x	10x	8x	10x	8x	10x	8x
Objective lens diameter	50mm	50mm	42mm	42mm	32mm	32mm	25mm	25mm
Minimum focus distance	5.5m	5.5m	4.0m	4.0m	2.0m	2.0m	1.5m	1.5m
Field of view	4.8°	5.0°	6.0°	6.3°	6.0°	7.8°	6.5°	6.2°
Exit pupil diameter	4.2mm	5.0mm	4.2mm	5.3mm	3.2mm	4.0mm	2.5mm	3.1mm
Relative brightness	17.6	25.0	17.6	28.1	10.2	16.0	6.3	9.6
Twilight factor	24.5	22.4	20.5	18.3	17.9	16.0A	15.8	14.1
Eye relief	15.5mm	19.5mm	15.5mm	19.5mm	16.0mm	15.5mm	12mm	15mm
Field of view at 1000m/yds	84m/yds	87m/yds	105m/yds	110m/yds	105m/yds	136m/yds	114m/yds	108m/yds

## PHYSICAL DIMENSIONS

Length	176mm	178mm	172mm	174mm	140mm	138mm	104mm	104mm
Width	133mm	133mm	128mm	128mm	124mm	124mm	108mm	108mm
Height	60mm	60mm	56mm	56mm	50mm	50mm	42mm	42mm
Weight	745g	740g	670g	665g	570g	565g	260g	260g



Product Video



Kowa Optimed Deutschland GmbH | Fichtenstrasse 123, | D-40233 Düsseldorf | Germany  
T: +49 (0) 211-542184-00 | E-mail: scope@kowaoptimed.com | www.kowaoptic.com