



2000 SabreLite™

This powerful flashlight was designed with one thing in mind: SAFETY. It carries a variety of approvals, allowing safe use in many different hazardous environments and conditions. The SabreLite is o-ring sealed with a twist-on shroud and comes with a polarity battery guard tray that safeguards against dangerous "outgassing" of hydrogen from an accidentally reversed cell. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures. Unlike ordinary flashlights that produce a yellow beam, the SabreLite's incredibly bright Xenon lamp produces a powerful white beam. Pelican's SabreLite is the leader in quality and performance.

- Built Pelican tough
- Submersible
- Super bright Xenon beam
- Unconditional Lifetime Guarantee of Excellence



DIMENSIONS

| | |
|--------|-----------------|
| Length | 7.79" (19.8 cm) |
|--------|-----------------|

MATERIALS

| | |
|-------------------------|--------------------|
| Body | EXL |
| O-Ring | Ethylene Propylene |
| Lens | Nylon |
| Shroud | Xenoy |
| Clip | ABS |
| Contact Spring Retainer | Stainless Steel |

COLORS

| | | |
|--------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
|  Orange |  High Visibility Yellow |  Black |
|--------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|

LIGHT SPECS

| | |
|-----------|----------------------|
| Lamp Type | Incandescent (Xenon) |
|-----------|----------------------|

POWER

| | |
|------------------|----------|
| Battery Size | C |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Volts | 4.5v |

WEIGHT

| | |
|--------------------------|------------------|
| Weight With Batteries | 12.8 oz (363 gr) |
| Weight Without Batteries | 5.3 oz (150 gr) |
| Packaged Weight | 6.8 oz (193 gr) |

SWITCH

Document created on 06-10-19






| | |
|--------------------|----------------------|
| Switch Type | Twisting Lens Shroud |
| Light Modes | On / Off |

CERTIFICATIONS

Class II, Division 2
IECEX ib
Class I, Division 1

OTHER

| | |
|---------------------|-----|
| Submersible | yes |
| Minimum Pack | 6 |
| Military | yes |
| Package Code | C |

| FL1 STANDARD | HIGH |
|-------------------------------------------------------------------------------------|--------------|
|  | 53 LUMENS |
|  | 5h 0mins |
|  | 158m |
|  | 6234cd |
|  | IPX7 |

ACCESSORIES