



ELECTRO-OPTICS - RED DOT

ROMEO-X

PISTOL-MOUNTED REFLEX SIGHT



COMPACT: SORX1200
Fits: P365 and, All Shield™ RMSc Footprints




PRO: SORX1000
Fits: Fits P320 and, All DeltaPoint® PRO Footprints



Forged 7075 Aluminum Housing



Low Deck Height For Standard-Height Iron Sight Co-Witness



Circle Dot With Individual Selectable 2 MOA Dot & 32 MOA Circle

ROMEO-X

PISTOL-MOUNTED REFLEX SIGHT

COMPACT: SORX1200 / PRO: SORX1000

- ▶ Inspired by MIL-SPEC ROMEO-M17
- ▶ Forged 7075 Aluminum Housing
- ▶ Patent-Pending Beryllium Copper Flexure Arm
- ▶ Distortion Free Aspherical Lens
- ▶ MOTAC (Motion Activated Illumination)
- ▶ Circle Dot With Individually Selectable 2 MOA Dot & 32 MOA Circle
- ▶ Low Deck Height for Standard-Height Iron Sight Co-Witness
- ▶ 20,000 Hour Battery Life With Side Load Battery
- ▶ 15 Illumination Settings Including 3 Night Vision
- ▶ Assembled in U.S.A.

	COMPACT	PRO
SKU#:	SORX1200	SORX1000
UPC:	798681686865	798681688180



ELECTRO-OPTICS - RED DOT

ROMEO-X

PISTOL-MOUNTED REFLEX SIGHT

Product Details				
SKU#	SORX1200 (Compact)		SORX1000 (Pro)	
Housing Material	Forged 7075 Aluminum			
Housing Finish	Black Anodized			
Clear Aperture Diameter (Measured Diagonally)	24 mm			
Lens Material	Glass			
Lens Type	Asphere			
Battery Type	CR1632			
Battery Location	Side			
Battery Access	Slotted Anti-Snag Cap		Slotted and Knurled Cap	
Battery Life in Hours at Medium Setting (Constant On)	20,000			
Emitter Type	High-Efficiency Point Source LED			
Windage Adjustment Range	80 MOA			
Elevation Adjustment Range	80 MOA			
Adjustment Resolution per Click	1.5 MOA			
Adjustment Screw Type	T6 Torx			
Tactile Adjustment Clicks	Yes			
Brightness Adjustment Settings	15 (12 Day / 3 NV)			
Reticle	2 MOA DOT / 32 MOA Circle			
Water Resistance	IPX-7			
Mounting Footprint	Shield™ RMsC		DeltaPoint® Pro	
Assembled In	USA			
Measurements	Imperial	Metric	Imperial	Metric
Overall Length	1.62 in	41.15 mm	1.83 in	46.48 mm
Overall Height	.94 in	23.88 mm	.94 in	23.88 mm
Overall Width	1.23 in	31.24 mm	1.23 in	31.24 mm
Weight w/ Battery	1.00 oz	28.35 g	1.15 oz	32.60 g



SIG SAUER®