



Core SX 10-40x56 CBR Riflescope

SPECIFICATIONS

| Magnification (x) | 10-40 |
|----------------------------------|---------------------|
| Objective lens diameter (mm) | 56 |
| Eye relief (in/mm) | 3.9 - 3.6 / 99 - 91 |
| Field of view (ft @100yd) | 9.9 - 2.5 |
| Tube diameter (mm/in) | 30 / 1.18 |
| Parallax setting (yds) | 15 - ∞ |
| MOA adjustment (one click =) | 1/8 MOA |
| Windage adjustment range (MOA) | 40 |
| Elevation adjustment range (MOA) | 40 |
| Battery type | CR2032 |
| Battery life (hours) | 100 - 70 |
| Focal plane | 2nd |
| Dimensions, in | 16.8 x 3.4 x 2.8 |
| Weight | 30.8 oz |

FEATURES

- Exposed locking turret
- Second focal plane reticle
- Red/Green illuminated reticle
- Single-piece, 30mm tube
- Aircraft grade aluminum
- Hard anodized finish
- Shockproof, fogproof, waterproof
- Fully multi-coated optics

INCLUDED

- Neoprene scope cover
- 30mm scope rings
- CR2032 battery

Designed for long-range hunting as well as recreational and competition shooting, the Sightmark Core SX 10-40x56 CBR Riflescope is a long-range problem solver. This high-powered second-focal-plane optic boasts a rugged, single-piece, hard-anodized 30mm 6061-T6 aircraft-grade aluminum tube; nitrogen-filled, IP67 waterproof and dustproof protection; fully multi-coated lenses; finely etched, red/green illuminated competition benchrest reticle with 5 brightness settings per color; exposed, locking turrets and 1/8 MOA windage/elevation adjustability. Includes a neoprene scope cover, 30mm rings and a CR2032 battery.