

SIGHT MARK®



Core TX 3-12x44DCR .223/.308 BDC Riflescope

SPECIFICATIONS

Magnification, x	3-12
Objective lens diameter, mm	44
Eye relief, in/mm	4 - 3.7 / 101.6 - 94
Field of view, ft @100yd	36.7 - 9.2
Tube diameter, in/mm	30 / 1.18
Parallax setting, yds	100
Windage/elevation adjustment range, MOA	70
MOA adjustment (one click=MOA)	1/4
Dimensions, in/mm	13 x 3.2 x 2.5 / 330.2 x 81 x 63
Weight, oz	20

FEATURES

- ✚ BDC reticle calibrated for .223 and .308 ammo
- ✚ Exposed, lockable turrets
- ✚ Red/green illuminated reticle
- ✚ Single-piece, 30mm tube
- ✚ Aircraft grade aluminum
- ✚ Hard anodized finish
- ✚ Shockproof, fogproof, waterproof
- ✚ Fully multi-coated optics
- ✚ Second focal plane reticle

INCLUDED

- ✚ Flip up lens covers
- ✚ 30mm scope rings
- ✚ CR2032 battery

Sightmark Core TX riflescopes use fully multi-coated optics to provide optimal light transmission in a variety of conditions. Etched glass reticles, in red or green, are illuminated to deliver optimal shot placement and are durable to withstand years of shooting. The Core TX riflescopes feature exposed, lockable turrets which help maintain a consistent zero. Turrets are quick and easy to adjust to compensate for bullet drop and windage on the fly. The Core TX 3-12x44DCR is housed in a durable 30mm tube, built from aircraft grade aluminum. This scope features a side focus adjustment, a duplex BDC reticle and is calibrated for .223 and .308 ammo.