

SIGHT MARK



PINNACLE SERIES

SPECIFICATIONS

Reticle type	TMD
Reticle color	Red/Green
Illuminated (yes/no)	Yes
Reticle brightness settings	5
Finish/color	Matte black
Magnification (x)	1-6
Objective lens diameter (mm)	24
Eye relief (mm)	103
Field-of-view (ft@100yd)	90-15.9
Diopter adjustment (+/-)	+3.5 to -3.5
Parallax settings (yds)	100
MRAD adjustment (1 click)	.1
Maximum recoil (G's)	800
Battery type	CR2032
Battery life (hrs)	Red: 50-1000 Green: 30-800
Focal plane	1st
IP standard (water rating)	IP67
Body material	Aluminum-6061
Tube diameter, mm	30
Operating temp. (°F)	-20 to 160
Dimensions (mm)	260x73.5x56
Weight (oz)	20.4

SIGHTMARK PINNACLE 1-6x24TMD RIFLESCOPE

FEATURES

- ✦ Premium, high-definition optics
- ✦ Precision machined in Japan
- ✦ Scratch-resistant lenses
- ✦ Constant eye relief
- ✦ 6:1 zoom ratio
- ✦ First-focal plane reticle
- ✦ Capped or exposed turret option
- ✦ Ballistic-matched BDC dials
- ✦ Red or green illuminated reticle
- ✦ Waterproof, fogproof, shockproof
- ✦ 30mm single piece tube
- ✦ Fully multi-coated optics

INCLUDED

- ✦ 5.56x45 55gr BDC dial
- ✦ 7.62x51 180gr BDC dial
- ✦ Turret caps (2)
- ✦ Thread protector (2)
- ✦ CR2032 Battery
- ✦ Manual