

SIGHT MARK®



PINNACLE SERIES

SPECIFICATIONS

Reticle type	TMD-HW
Reticle color	Red/Green
Illuminated (yes/no)	Yes
Reticle brightness settings	5
Finish/color	Matte black
Magnification (x)	5-30
Objective lens diameter (mm)	50
Eye relief (mm)	97-96
Field-of-view (ft@100yd)	6.7-1.1
Diopter adjustment (+/-)	+2 to -2
Parallax settings (yds)	30 - ∞
MRAD adjustment (1 click)	.1
Maximum recoil (G's)	800
Battery type	CR2032
Battery life (hrs)	Red: 50-1000 Green: 30-800
Focal plane	1st
IP standard (water rating)	IP67 - submersible to 1m
Body material	Aluminum
Tube diameter, mm	34
Operating temp. (°F)	-20 to 160
Dimensions (mm)	357x92.9x79.9

SIGHTMARK PINNACLE 5-30x50 TMD

FEATURES

- ✦ Premium Japanese glass
- ✦ Fully multi-coated optics
- ✦ Scratch-resistant lenses
- ✦ Zero stop elevation dial
- ✦ Constant eye relief
- ✦ 6:1 zoom ratio
- ✦ First-focal plane reticle
- ✦ Capped or exposed turret option
- ✦ Fast focus eyepiece
- ✦ Red or green illuminated reticle
- ✦ Waterproof, fogproof, shockproof
- ✦ 34mm single piece tube

INCLUDED

- ✦ Sunshade
- ✦ Turret caps (2)
- ✦ Thread protector (2)
- ✦ CR2032 Battery
- ✦ Manual