

SIGHT MARK®



SPECIFICATIONS

Magnification (x)	1
Field of view (m @ 100m)	40
Objective lens diameter, mm	24
Body material	Glass filled nylon composite
Focus range (m)	0.24 to infinity
Diopter setting (D)	+2, -6
Waterproof (yes / no)	Yes
Battery life (hour)	50
Battery and Voltage	AA / 1.5 V
Operating temp.	-51 to +49 °C
Dimensions (in)	4.5x2.25x2
Weight (oz)	12.4

PVS-14 ITT Pinnacle Gen3

FEATURES

- ⊕ Auto-Gated, thin film ITT Pinnacle tube
- ⊕ Automatic brightness control
- ⊕ Head mountable, hand held, weapons mountable
- ⊕ Variable gain control
- ⊕ Extremely versatile
- ⊕ Single AA battery operation
- ⊕ Integrated IR illuminator
- ⊕ Low battery indicator
- ⊕ IR illuminator on indicator

INCLUDED

- ⊕ Head mount
- ⊕ Soft carrying case
- ⊕ Day light filter
- ⊕ Demist Shield
- ⊕ Sacrificial window
- ⊕ Batteries
- ⊕ Head mount adapter
- ⊕ Brow pads (small, medium, large)
- ⊕ Data sheet
- ⊕ Eyecup

GEN III IMAGE INTENSIFIER TUBE

Photocathod type	18mm GaAs
Photocathode Sensitivity (minimum)	1350
Resolution, lines per mm	64
Gate type	Auto-gated
Signal-to-noise-ratio (not less than/ typical)	16.2/21
Film type	Thin-Filmed
Brightness Gain, fL/FL	25 to more than 3,000

The **Sightmark PSV-14 Gen 3 Night Vision** allows the user superior depth perception for surveillance functions and extended wear.