

# Sightmark Triple Duty 4-16x44 Riflescope DX

SM13017DX



## DESCRIPTION

Equipped with an illuminated red/green Duplex reticle, the Sightmark® Triple Duty 4-16x44 DX Riflescope aids in range estimation and hunting fast-moving varmints at long distances. Its cutting-edge glass and fully multi-coated optics transmit a bright, crisp image that makes tracking and shooting targets almost effortless. The Triple Duty 4-16x44 DX Riflescope features a one-piece 30mm tube that delivers exceptional light transmission and a wide field-of-view. O-ring sealed and nitrogen-purged, the precision scope is both fog proof and water resistant. The included oversized, locking windage and elevation turrets with 1/8-inch MOA clicks provide an additional level of accuracy and ensures that the scope stays zeroed. The Triple Duty series of riflescopes are complimentary to any shooter's arsenal.

## FEATURES

- Weatherproof, shockproof, fogproof
- Windage/Elevation adjustment lock
- Second focal plane reticle (true at 10x)

- Etched reticle
- 30mm main tube
- Red and green reticle illumination

## SPECIFICATIONS

Reticle	Dot Duplex
Reticle, Type	Etched
Reticle, Color	Black and green
Reticle, Illuminated	yes
Setting, Brightness	0 - 5
Finish/Color	Matte black
Magnification	4 - 16
Diameter, Objective Lens	44
Diameter, Eyepiece	37
Diameter, Exit Pupil	11 - 2.75
Eye Relief	120.1 - 88.4
Field of View	9.61 - 2.44
Field of View	31.5 - 8
Diopter Adjustment	2 to -3
Diameter, Tube	30
Tube Piece (single/two)	single
Parallax Setting	12 to infinity
Windage Range of Adjustment	60
Elevation Range of Adjustment	60
Windage & Elevation, Lock	yes
MOA Adjustment	1/8

Maximum Recoil	1,200
Battery Type	CR2032
Battery Life	(high) 80 - (low) 150
Battery Voltage	3
Sunshade	yes
Nitrogen Purged	yes
Shockproof	yes
Fog Proof	yes
Focal Plane	2nd
IP Standard	IP66
Body Material	6061 Aluminum
Material, Lens	K、ZF、 ZK
Lens Coating	Fully multi-coated
Mount Type	Weaver
Operating Temp, ♦F/♦C	-20 to 140 / -29 to 60
Storage Temperature (°C/°F)	41 to 95 / 5 to 35
Length	14.8 / 376
Width	3.34 / 85
Height	3 / 75
Weight	28.2

Print friendly version