

MEGASTREAM® HP USB

LITHIUM-ION RECHARGEABLE HIGH CANDELA FLASHLIGHT

DESCRIPTION: The MegaStream® HP USB is powered by (1) Streamlight SL-B34® lithium-ion rechargeable battery pack delivering 1,350 lumens and 310,000 candela. It features a tail cap switch, momentary or constant on operation, high/medium/low beams, a pocket clip for convenience, and amazing candela & beam distance capability for a light of its size. The anodized aluminum housing makes the light extremely durable and abrasion resistant. To charge the light, slide the head cover back to expose the USB-C port.

CASE MATERIAL: Machined aluminum alloy case. Type II MIL-Spec anodized finish. Available in Black.


DIMENSIONS: Length: 6.61 in (168 mm) Body Diameter: 1.0 in (25 mm) Head Diameter: 2.24 in (57mm)

WEIGHT: 9.0 oz (254g) with battery (included with purchase).

LENS: Glass lens.

LIGHT SOURCE: LED technology, impervious to shock with a 30,000-hour lifetime.

LIGHT OUTPUT: High: 1,350 lumens, 310,000 candela peak beam intensity, 1114m beam distance.
Med: 470 lumens, 108,000 candela peak beam intensity, 657m beam distance.
Low: 145 lumens, 32,000 candela peak beam intensity, 358m beam distance.



ON/OFF: Push-button tail switch with momentary or constant on operation.

RUN TIME:  High: 2 hours; Medium: 4 hours; Low: 15 hours
All run time claims are to 10% of initial lumen output.

BATTERY: (1) 3,500mAh Streamlight SL-B34® lithium-ion cell with on-board safety circuit.
Fully recharges in 5 hours and charges battery in product.
Charge indication LED: Red - Charging; Green - Charged.

FEATURES: LED technology for extreme candela.
IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.
Knurled body for improved grip
Self-keying battery ensures proper alignment of the charging port.
1-meter impact resistance tested.
Removable pocket clip.
Holster and USB-C cord included.



APPROVALS:  Meets applicable United Kingdom and European Community Directives
 CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL ACCESSORIES: USB/AC adapter(s)

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		1,350 LUMENS	470 LUMENS	145 LUMENS
RUN TIME		2h	4h	15h
DISTANCE		1114 m	657 m	358 m
INTENSITY		310,000 cd	108,000 cd	32,000 cd

All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 4/8/2025

Revised:

Rev:

Engineered in the USA; Made in China.

Document #434