



# RANGEFINDER

## COMPARISON SHEET



**RAZOR®**  
HD 4000 GB



**VIPER®**  
HD 3000



**DIAMONDBACK™**  
HD 2000



**CROSSFIRE™**  
HD 1400

| CONFIGURATION         | 7x25   | 7x25  | 7x24  | 5x21  |
|-----------------------|--|---|---|---|
| OPTIC DISPLAY         |  |   |   |   |
| RANGE                 | Max Reflective: 4000 yds.<br>Tree: 2500 yds.<br>Deer: 2200 yds.<br>Minimum: 5 yds.           | Max Reflective: 3000 yds.<br>Tree: 2300 yds.<br>Deer: 2000 yds.<br>Minimum: 6 yds.      | Max Reflective: 2000 yds.<br>Tree: 1800 yds.<br>Deer: 1400 yds.<br>Minimum: 5 yds.    | Max Reflective: 1400 yds.<br>Tree: 950 yds.<br>Deer: 750 yds.<br>Minimum: 5 yds.      |
| ACCURACY:             | +/- .5 yds. (@100yds.)   | +/- 1 yd. (@100yds.)  | +/- 1 yd. (@100yds.)  | +/- 1 yd. (@100yds.)  |
| FIELD OF VIEW:        | 341' (@1000yds.)   | 314' (@1000yds.)  | 335' (@1000yds.)  | 367' (@1000yds.)  |
| SIZE (LXW):           | 4.4" x 1.7"  | 4.2" x 1.7"   | 4.4" x 1.8"   | 4.0" x 1.3"   |
| WEIGHT:               | 9.9 oz.  | 9.1 oz.   | 7.6 oz.   | 4.8 oz.   |
| RANGING MODES         | Line of Sight<br>Horizontal Component Distance<br>Scan Feature                               | Line of Sight<br>Horizontal Component Distance<br>Scan Feature                          | Line of Sight<br>Horizontal Component Distance<br>Scan Feature                        | Line of Sight<br>Horizontal Component Distance<br>Scan Feature                        |
| TARGET MODES          | Normal<br>First<br>Last<br>ELR   | Normal<br>First<br>Last<br>ELR  | Normal<br>-<br>Last<br>-  | Normal<br>First<br>Last<br>-  |
| OPTICAL FEATURES      | HD Optical System<br>XR™ Plus Lens Coating   | HD Optical System<br>XR™ Plus Lens Coating  | HD Optical System<br>XR™ Lens Coating   | HD Optical System<br>XR™ Lens Coating   |
| CONSTRUCTION FEATURES | Magnesium Chassis<br>ArmorTek®<br>Rubber Armor<br>Waterproof<br>Shockproof                   | Aluminum Chassis<br>ArmorTek®<br>Rubber Armor<br>Waterproof<br>Shockproof               | Polymer Chassis<br>ArmorTek®<br>Rubber Armor<br>Waterproof<br>Shockproof              | Polymer Chassis<br>ArmorTek®<br>Waterproof<br>Shockproof<br>-                         |
| PERFORMANCE FEATURES  | Red Backlit LCD Display<br><.25 Second Measuring Time<br>Ranging Format yds/m<br>CR2 Battery | Red OLED Display<br><.25 Second Measuring Time<br>Ranging Format yds/m<br>CR123 Battery | Red OLED Display<br><.25 Second Measuring Time<br>Ranging Format yds/m<br>CR2 Battery | Red TOLED Display<br><.5 Second Measuring Time<br>Ranging Format yds/m<br>CR2 Battery |
| CONVENIENCE FEATURES  | Adjustable Eyecups<br>Diopter<br>Hard Carry Case<br>Utility Clip<br>Tripod Adaptable         | Adjustable Eyecups<br>Diopter<br>Soft Carry Case<br>Utility Clip<br>Tripod Adaptable    | -<br>Diopter<br>Soft Carry Case<br>Utility Clip<br>Tripod Adaptable                   | -<br>Diopter<br>Soft Carry Case<br>-<br>-   |