



STRIKE EAGLE[®]

RIFLESCOPE



PRODUCT MANUAL

THE STRIKE EAGLE® RIFLESCOPE

The need for high-performance, precision optics is the driving force behind all we do. And your Strike Eagle® is a prime example. Incredibly versatile and feature rich, there is little this scope won't do. A 6X zoom range, exposed tactical turrets purpose-built for dialing precision long-range shots, an illuminated, glass-etched reticle, and stunning, fully multi-coated optics combine to make this scope the perfect choice for your shooting needs.



- 1** Eyepiece/
Ocular Lens
- 2** Fast-Focus Eyepiece
- 3** Locking Elevation Turret
- 4** Side Focus Knob
- 5** Illumination
Control Knob
- 6** Objective Lens
- 7** Windage Turret
- 8** Magnification
Adjustment Ring

Please read the entire manual before using your new optic. Images are for representation only. Product may vary slightly from what is shown.

RIFLESCOPE ADJUSTMENTS

Reticle Focus Adjustment

The Strike Eagle® riflescope uses a fast-focus eyepiece, designed to quickly and easily adjust the focus on the riflescope's reticle.

To adjust the reticle focus, look through the riflescope at a blank white wall or up at the sky. Turn the eyepiece focus dial in or out until the reticle image is as crisp as possible. Try to do this quickly, as your eye will try to compensate for an out of focus reticle.

Once this adjustment is complete, it is not necessary to refocus every time the scope is used. However, as your eyesight may change over time you should recheck this adjustment periodically.

WARNING: Looking directly at the sun through a riflescope, or any optical instrument, can cause severe and permanent damage to your eyesight.



Adjust the reticle focus.



Rotate ring to adjust the magnification.

Variable Power Adjustment

To change the magnification, turn the magnification ring to the desired level.

Illumination Adjustment

The Strike Eagle® riflescope uses an illuminated reticle to aid in low-light performance. Illumination intensity levels will vary from bright to very low, with 11 total levels of brightness.



Windage and Elevation Adjustments

Your riflescope features adjustable elevation and windage turret dials with audible clicks. Each audible click moves the bullet's point of impact 1/4 of a Minute of Angle (MOA). 1/4 MOA closely corresponds to 1/16 in. at 25 yds., 1/8 in. at 50 yds., 1/4 in. at 100 yds., and 1/2 in. at 200 yds.

EXAMPLE: It will take four (4) clicks to move the bullet's point of impact approximately one inch at 100 yds.

To make turret adjustments:

1. Turn the turret in the appropriate direction: up/down or left/right as indicated by the arrows.
2. Following the directional arrows, turn the dials in the direction you wish the bullet's point of impact to go.



Indexing Adjustment Dials with Zero Reset

This riflescope features Windage and Elevation dials that allow you to reindex the zero indicator after sight-in without disturbing your settings. Though not a required process, resetting the Windage and Elevation dials allows you to quickly return to your original zero if you dial temporary corrections in the field.

To reset the Windage and Elevation dials:

1. While firmly holding the turret knob, loosen and remove the center screw. DO NOT allow the turret to rotate.
2. With the center screw removed, lift and remove the turret knob.
3. Reinstall the turret knob by aligning the "0" mark with the indicator line.
4. Replace the center screw.

Using the Side Focus

Parallax is a phenomenon that results when the target image does not quite fall on the same optical plane as the reticle within the scope. When the shooter's eye is not precisely centered in the eyepiece, there can be apparent movement of the target in relation to the reticle, which can cause a small shift in the point of aim. Parallax error is most problematic for precision shooters using high magnification.

Select Strike Eagle® riflescopes feature a side focus dial to adjust for maximum image sharpness and eliminate parallax error. Models without the side focus adjustment are factory-focused at a distance of 100 yds.

Setting the side focus:

1. Be sure the reticle is correctly focused (see *Reticle Focus* on page 3).
2. Turn the side focus adjustment dial until the target image is as sharp as possible.
3. Check for parallax error by moving your head back and forth while looking through the scope. The focus is correct if there is no apparent shift of the reticle on the target. If you notice any shift, adjust the focus knob slightly until all shift is eliminated.



Adjust the side focus dial.

Battery Replacement

To change the battery, unscrew outer cap with a coin. Remove the battery and replace with a new CR2032 battery with numbers facing out.



MAINTENANCE

Cleaning

Your Vortex® riflescope requires very little routine maintenance other than periodically cleaning the exterior lenses. The exterior of the scope may be cleaned by wiping with a soft, dry cloth. When cleaning the lenses, be sure to use products that are specifically designed for use on coated optical lenses.

- Be sure to blow away any dust or grit on the lenses prior to wiping the surfaces.
- Using your breath, or a very small amount of water or pure alcohol, can help remove stubborn things like dried water spots.

Lubrication

All components of the riflescope are permanently lubricated, so no additional lubricant should be applied.

NOTE: Other than removing the turret caps, do not attempt to disassemble any components of the scope. Disassembling the scope may void the warranty.

Storage

If possible, avoid storing your scope in direct sunlight or any very hot location for long periods of time.



VIP WARRANTY

OUR UNCONDITIONAL PROMISE TO YOU.

We promise to repair or replace the product. Absolutely free.

- ▶ **Unlimited**
- ▶ **Unconditional**
- ▶ **Lifetime Warranty**

Learn more at VortexOptics.com
service@VortexOptics.com • 800-426-0048

Note: The VIP Warranty does not cover loss, theft, deliberate damage, or cosmetic damage not affecting product performance.



M-00149-1

© 2020 Vortex Optics

® Registered Trademark and TM Trademark of Vortex Optics.

Patent Pending